

REBOUND LINE MARKING – AS Available in White, Yellow, Blue & Red

Description:

Rebound Line Marking – AS is a high opacity water based acrylic coating suitable for linemarking on all water based Rebound Topcoat surfaces. It is specially designed to have the same slip and play characteristics as the court surface.

Rebound Line Marking – AS can be applied by brush, spray or mini-roller. International Tennis Standards Linemarking Specification is for white 50 mm width lines. For spray application it can be diluted up to 10 % with water where required.

For high definition lines with “sharp” edges, **Rebound Line Sharp** can be used in conjunction with conventional tape systems.

Rebound Line Sharp:

Rebound Line Sharp is a 100% acrylic clear sealer used to seal taped edges when linemarking to produce a clean crisp line edge.

Application Procedure:

1. Prior to applying line marking, make sure the topcoat surface is clean and free from dust and loose material.
2. Mark out court lines using a chalked string line.
3. Apply tape using a tape machine ensuring lines are straight and the tape is compressed to achieve good contact with the topcoat surface.
4. Apply **Rebound Line Sharp** directly from the container. Using a paint brush or mini-roller, apply over the tape edge to seal the edge to minimise any bleed under the tape when applying the white line marking coating.
5. Allow sealer to cure. The sealer will be clear when cured and can take from 10-30 minutes depending on ambient conditions.
6. Apply the White line marking paint by brush or mini-roller being careful to stay within the tape and avoid spillage onto the play area.
7. Allow line marking to dry then remove tape.

NB The use of **Rebound Line Sharp** is optional, and is used to produce a crisp line edge.

Coverage:

Rebound Line Marking – AS: 2 to 3 litres per standard tennis court
Rebound Line sharp: 1 to 2 litres per standard tennis court